



Guangzhou Harley Commodity Company Limited
Model: # L-108 NIOSH 42 CFR part 84

USE INSTRUCTIONS


1. Failure to follow all instructions and limitations can seriously reduce the effectiveness of this respirator and could lead to illness, injury or death.
2. A properly selected respirator is essential. Before occupational use, the wearer must be trained by the employer in the correct use of the respirator in accordance with applicable safety and health standards.
3. This product does not supply oxygen. Use only in adequately ventilated areas containing sufficient oxygen to support life.
4. Discard the respirator and replace with a new one if:
 - A. excessive clogging of the respirator causes breathing difficulty
 - B. the respirator becomes damaged.
5. Leave the contaminated area if dizziness, irritation or other distress occurs.
6. Keep respirators in the display box away from direct sunlight until use.
7. Before occupational use of this respirator, a written respiratory protection program must be implemented meeting all the local government requirements. In the United States, employers must comply with OSHA 29 CFR 1910.134 which includes medical evaluation, training, and fit testing.
8. Before wearing the mask, respirator users must check whether there is crack or spot around the welding spot. If yes, this mask must be discarded at once and can not be used again.

USE LIMITATIONS

1. Do **NOT** use the respirator or enter or stay in a contaminated area under the following circumstances:
 - a. Atmosphere contains less than 19.5% oxygen.
 - b. If you smell or taste a contaminant.
 - c. For protection against gases or vapors.
 - d. Contaminants or their concentrations are unknown or immediately dangerous to life or health.
 - e. Concentrations of contaminants exceed maximum use concentrations in applicable OSHA standards or applicable government regulations or 10 times the PEL (Permissible Exposure Limit), whichever is lower.
 - f. For sandblasting, paint-spray operations asbestos.
 - g. Use in explosive atmospheres.
2. Do **NOT** modify or misuse the respirator.
3. Do **NOT** use the respirator with facial hair or any other conditions that may prevent a good face-seal.

Donning & Fitting Instructions

1. Open the respirator with both hands
2. Cup the respirator firmly against your face with the nosepiece on the bridge of your nose.
3. Stretch and pull the lower headband over the head and position below your ears. Stretch and pull the top headband on the back of your head above your ears
4. Press soft metal or plastic nosepiece to conform snugly around your nose.
Using both hands press the nose piece to conform snugly around the nose.
Using only one hand may not ensure a uniform seal.
5. Seal check:
 - To test the fit of a respirator without an exhalation valve, cup both hands over the respirator and exhale sharply.
 - To test the fit of a respirator with an exhalation valve, cup both hands over the mask and inhale sharply. A negative pressure should be detected inside the respirator.
 - If air flow is felt in the nose area, re-adjust/tighten the nose clip.
 - If air flow is felt around the edges of the respirator, re-position the respirator/head strap to achieve a better fit.
6. Change the mask immediately if breathing becomes difficult or mask becomes damaged or distorted.
7. Change the respirator if a proper face seal can not be achieved.
8. Careful observance of these instructions is an important step in safe respirator use.



1



2



3



4

Protection:

- N-series filters are effective against particle aerosols free of oil.
- N95-Particulate Filter (95% filter efficiency level) effective against particulate aerosols free of oil.

Guangzhou Harley Commodity Company Limited

(Plant A01) Yuanzhongang Village, Taiping Town, Conghua District,

Guangzhou, China

TEL: 0086-20-37512950

FAX: 0086-20-37512951